



the right fixing

SPIT 335



joiners



plumbers/
heating specialists



builders



steel fabricators



electricians



powerlines and
networks

Electro Pneumatic Combi Hammer SPIT 335



drilling capacity	drilling Ø	weight	power	impact force
Ø 4 → Ø 30	Ø 14 → Ø 24	3.9 kg	750 W	3.5 J

accessories

standard concrete drill bit SDS +

triangular shank concrete drill bit

triangular shank hollow core cutter

wood auger bit S2S

Ø6 → Ø15 mm

Ø16 → Ø30 mm

Ø45, Ø55, Ø66, Ø68 mm

Ø6 → Ø30 mm

pick SDS+

pick

chisel SDS+

chisel

triangular shank gouge

triangular shank gouge bolster

features

- Can be used with various tools for many types of jobs (wood, steel, concrete, picking, chiselling, etc.) with adjustable chuck.
- Select speeds 1 to 6 to adapt the rotation speed and impact force to the material and job.
- Light indicates when servicing should be performed.
- Chisel can be adjusted to different position for easier work.
- Safety clutch.

technical data

Input power	: 750 W
Output power	: 440 W
Volt	: 230 V
Ampere	: 3.3 A
Frequency	: 50 - 60 Hz
Rotation speed under load	: 280 at 650 tr / mn
Impact rate	: 1650 at 3900 mn
Wire length	: 4 meters
Tool holder	: SDS standard

The use of our products must conform strictly to the operating and safety instructions in the technical and user manuals.



ITW Asia (Pte) Ltd

8 Kaki Bukit Road 2, #02-34, Ruby Warehouse Complex, Singapore 417841
Tel: +65 6746 1177 Fax: +65 6746 1482 Email: itwasia@singnet.com.sg Website: www.itwasia.com

Brochure Reference Number: ITW07-015